

Performance technology innovates with high yield spray foam to insulate buildings and homes.



**Closed Cell Spray Foam**  
Integrity  
High R-Value  
Strong Yield  
Consistent flow  
Eco Earth certified  
Made in USA

EPS 2000 is a two component closed cell spray-applied semi-ridged structural foam with thermal and vapor properties. Another green product from EcoPolySeal, it complies with our green initiative with an earth friendly composition. Recognized as a world-class spray foam that creates an envelope sealing all cracks, cavities, stud walls, perimeter joists, cathedral, roof and garage ceilings. This product is designed to be install by a certified EcoPolySeal installer in the interior of commercial buildings and homes.

Properties	Tested Value	Testing Code
R-Value	6.9 Winter 6.7 Summer	ASTM C518
Green Certified	Pass	UL Environment (Greenguard Gold)
Density	2.17 lb Winter 2.23 lb Summer	ASTM D1622
Vapor Permeance	1.1 Winter 1.625 Summer	ASTME 96
Air Permeance	<.02 L/sm	ASTME 2178
System Air Leakage	.001-.0039	ASTME 2357
Tensile Strength	37.9 Summer 53.7 Winter psi	ASTM D-1623
Fungi Mold	Pass	ASTM C 1338
Surface Burning	S-Flame 0-5 S-Smoke 350-400 W-Flame 5 W-Smoke 250-400	ASTM E84
Ignition Barrier X	Pass	AC377
Thermal Barrier	Pass	NFPA 286

Success guarantee. We guarantee customer satisfaction with our world-class spray foam insulation. Innovation and technology are instrumental in manufacturing leading edge technology spray foam. EcoPolySeal authorized installers, our building and home owners and the EcoPolySeal team are considered one family. We guarantee success and satisfaction on your insulation job. We back it up with our limited lifetime warranty!